

"SMART is the right way to do something in the Lab as well."

Some tens of equipment are required in the lab for any kind of chemical or biological experiment. A fact is that a scientist has to walk around in the lab periodically and monitor every equipment to watch if the experimental procedure is going well without any problem.

In spite of the limited manpower, time and space, scientists have a common mission to get the best result in their experiments, and it's not a simple issue to incorporate a certain innovative way to improve laboratory productivity.

Now, DAIHAN Scientific is going to take an initiative to change existing situation in the labs. So called, **Smart-Lab™ Equipment** is being introduced now here for the first time in the world, which will definitely *change the way to work in the labs.*

Wisd ²/₂ Smart-Lab[™] Equipments



"Remote Laboratory" - No limitation on Time and Place

 It's possible to monitor and control Wisd 22 Smart-Lab[™] Equipments through App or Web at any time and anywhere you are.

"Intuitive Use" - Easiest way to monitor and control

- · You would have Innovative User Experience on the full touch-screen LCD controller
- All the equipments in a lab, or, even in multiple labs, can be controlled at your fingertips using Smart phone or Laptop.

"Secure Laboratory" - Self-diagnostics & Real-time notification

• Based on Self-Diagnostic System, any operational error of the equipment is noticed to the user and to the Service Center, automatically.



Maximum Convenience by Advanced Digital Technology

Smart-Lab[™] Equipments



Like your Smart Phone in hand, and Smart TV at Home, Now, the Various Kinds of Equipment in Your Lab can be SMART!!

Make your Works and Laboratories SMART with DAIHAN Smart-Lab[™] Equipments & WiRe[™] App & Web Service.

DAIHAN Smart-LabTM Equipments

The Smart-Lab[™] System is an innovation of laboratory equipments.

DAIHAN Smart-Lab[™] equipments include two types controller, 4-inch or 7-inch, full-touch screen controller, integrating the most extensively applied Android System and Internet Connectivity. At anytime, anywhere you are, and anyhow, you can check and control all the equipments in your lab using your smart phone, tablet on the web.

No Button. No Knob. Simply Touch!! DAIHAN SMART line of Lab Equipments with **Full Touch Screen Controller** and **Internet Connectivity!!**

>>> Features

- 4" or 7" Full Touch Screen TFT LCD
- Ergonomic Design for Intuitive User Interface
- Program Control : Multiple Pattern with Multiple Segments
- Data Recording : On-Screen Temperature Chart
- USB storage for Recorded Data
- Internet Connectivity with WiFi
- Remote Monitoring and Control by WiRe[™] Service
- Storage Management function : Record the location of samples in the chamber and find easily afterwards, on screen (for ULT Freezers)
- Self-Diagnostic Function : Automatic Check & Alarm for the Failures in Key Parts
- Real-time Notification of any Failure in the Equipment to the User(s), to the Service Man and to Supplier, through WiRe[™] Service



DAIHAN Smart-Lab™ Controller

The DAIHAN Smart-Lab[™] Controller is embedded in all of Wisd Smart-Lab[™] equipments, which has a lot of useful functions like data recording, Storage managment, and self-diagnostic function and so on.

These functions are unique and innovative in the laboratory equipments. And the controller is connected with researcher's Smart phone, tablet or laptop computer through internet, by WiFi, so scientists are able to check all the equipments in the laboratory at any time, and at any place.

Error I	Jul 11, 2013 2:53:42 AM 💎
GRAPH	OFFSET
SETUP	5 . STORAGE
SET TEMP	J C STOP
-95 c	LCO2
OPERATION O CO	OMP #1 🤤 COMP #2



Sel	ect	Pattern		Repeat Count	:1	Select I	Attern Link
No		Start Segment		End Segment		Count	Delete
01		No Segment I		No Segment 1		No Count 1	Delete
02		No Segment 1		No Segment !		No Count I	
03		No Segment I		No Segment I		No Count I	
04		No Segment 1		No Segment (No Count I	
	G	Select Segment	T	Select Segment	T	Count	





>>> Ergonomic Screen Design

- 4″ or 7″ Full Touch Screen TFT LCD
- Intuitive User Interface
- No-extra Button, Knob or Switch
- All the main Functions and Parameters are displayed on the Main Screen.
- · Simple Touch to set the Temperature, Time, and other parameters

>> Automatic Data Recording

- High Resolution Graphic Display
- On-Screen Temperature Chart : Check the Temperature Record Graph on the Screen and could see the Details by Zoom-in & Zoom-out enabled at your finger tips.
- The Recorded Data could be transferred to PC by USB Memory.

>> Program Control

- · Variable Program Setting for Multiple Patterns with Multiple Segments
- · Preview window offered to check simply the input patterns
- Very easy to input and edit patterns

>> Self Diagnostic Function

- · Automatic Check & Alarm for the Failures in Key Parts of the equipment
- Real-time Notification of any Failure in the Equipment to the User(s), to the Service Man and to Supplier, through WiRe[™] Service.
- Implemented by LIN and empowered by WiRe[™] Service

>> Internet Connectivity with WiFi

- Remote Control is available for all the Equipments in the laboratory using Smart Phone, tablet or on the Web.
- Available WiRe[™] App & Web Service



Maximum Convenience by Advanced Digital Technology

Smart-Lab[™] Equipments



WiRe[™] App & Web Service



WiRe[™] App & Web service enables gathering, analyzing, and sharing of experimental data, and direct control of the unit is possible as well, anywhere and at any time.

When a defect of the unit occurs, it is processed by selfdiagnostic system automatically. If you want to get safe and reliable data comfortably, it's a Smart choice to be Supported by WiRe[™] service.

At anytime, Anywhere you are, and Anyhow, you can check and Control All the Equipment in your Lab **Using Your Smart Phone or on the Web.**

>> Features

- Developed by Advanced Web Technology
- · Support all different kinds of Web browser based on HTML Standards
- Available in all the PCs, Laptops and MACs
- Offering Android App and Apple iOS App
- Almost same UI as the Touch Screen Controller on the Equipment is available



OP-02:00

Ö

Unit ID DuoFreez-U300-001

Operation Mode Fixed

Stop

»> WiRe[™] Remote Control System

- Anytime, anywhere you are, and anyhow, you can check and control the Freezer in your Lab using your smart phone or web.
- It is possible to monitor and control the Smart-Lab[™] equipment through all smart phone, tablet and web without restraint of time and place.

>>> Device Settings and User Registration

- A single unit can be remote controlled by multiple users
- A single user can remote control multiple units in the Lab
- Smart-Lab[™] equipments offer registration of multiple users with simple account information



Timer

DuoFreez U300, Running...

°C

6

- 95.0

2

>> Self Diagnostic Function

The Self-Diagnosis System senses a certain defect within the unit, and reports it to the service center through the servers operated by DAIHAN. The Service Center verifies the defects of the unit received, and could offer prompt service.



>>> Smart-Lab™ Equipment lines

Display Error Status Reporting

ThermoStable [™] SIG- / SIF-Series of General Purpose Incubators	P.112~113, 116~117
ThermoStable [™] SIR-Series of Low Temperature Incubators	P.126~127
ThermoStable [™] SON-/SOF-Series of General Purpose Ovens	P.148~149, 152~153
ThermoStable [™] SOV-Series of Vacuum Ovens	····· P.160
ThermoStable™GC-Series of Growth Chambers	···· P.48~49, 130~131
SimpleFreez [™] & DuoFreez [™] -Series of Ultra Low Temperature Freezers	P.166~181
SMART Refrigerated Bath Circulators	Coming soon
SMART Shaking Incubators	Coming soon
SMART Temp. & Humidity Chambers	5
SMART Cold Lab Chambers	Coming soon

DAIHAN ThermoStable[™] SIG SMART Incubators, Gravity Convection-type, 32-/50-/105-/155 Lit. € with Smart-Lab[™] Controller, 4[″] Full Touch Screen, Fuzzy-PID Control, up to 70°C, ±0.2°C, with Certi. & Traceability



SMART Incubator, Forced Convection-type "ThermoStable SIG-105"



The Best Temp. Uniformity & Accuracy by High Performance Heating Mechanism



Display of Smart-Lab[™] Controller

* See page 6 ~ 11 for the Feature of Smart-Lab[™] System

- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Optimized Air Circulation by Natural Flow preventing Cross **Contamination of Samples**
- Smart-Lab[™] Controller
- UL/CUL Certified
- CE Certified GD(Good Design)-mark
 - PL(Product Liability) Insurance
- * Various Application : Microorganism Culture, Animal & Plant Cell Culture, Constant Temp., Germination, and so on
- * The Best Temp. Uniformity & Accuracy by High Performance Heating Mechanism: 3-Side Heating
- * Optimized Air Circulation by Natural Flow preventing Cross Contamination of Samples
- * Ergonomic Design 4["] Full Touch Screen TFT LCD(Smart-Lab™Controller)
- * WiRe[™]App & Web Service. * Automatic Data Recording
- * Self-Diagnostic Function * 2ea of Teflon-coated steel Wire Shelves Included
- * Variable Program Setting for Multiple Patterns with Multiple Segments
- * The Recorded Data could be transferred to PC by USB memory
- * Controller SW can be upgraded through USB port.
- * Compact New Body Design * Internet Connectivity with WiFi
- * RS232C Interface for Monitoring and Controlling with PC
- * Ambient to 70℃ of Temp. Range, Fluctuation of ±0.2℃ at 37℃, ±0.3℃ at 50℃
- * Corrosion Resistant 304 Stainless steel Chamber
- * Over Temperature & Over Current Protection, Sensor Error Detection

Specification

Models		ThermoStable SIG-32	ThermoStable SIG-50	ThermoStable SIG-105	ThermoStable SIG-155		
Capacity		32 Lit.	50 Lit.	105 Lit.	155 Lit.		
Dimension	Interior (mm)	312×290×360	370×350×420	485×410×535	550×475×600		
$(w \times d \times h)$	Exterior (mm)	458×477×624	518×537×701	635×595×841	700×660×906		
Heater Power		150W	200W	300W	400W		
	Range	Ambient Temperature +5 °C to 70 °C					
T	Fluctuation	\pm 0.2 °C at 37 °C , \pm 0.3 °C at 50 °C					
Temp.	Variation	± 0.6℃ at 37℃, ± 1.0℃ at 50℃					
	Sensor	PT 100					
Control Resolut	ion	±0.1℃					
Heat-up Time		25 min. to 37 °C, 40 min. to 50 °C			30 min. to 37 ℃, 40 min. to 50 ℃		
Recovery Time (Door open 30sec)			8 min. to 37 °C 12 min. to 50 °C 15 min. to 50 °C				
Controller		Smart-Lab [™] Controller					
RS232 Port		Available to connect with PC					
Display		4" Full Touch Screen TFT LCD					
Timer		99hr 59 min (delay/continuous function)					
	Internal	Stainless steel (#304)					
Material	External	Powder Coated steel					
	Inner Door	Inner Tempered Glass Door					
Shelves		2ea of Teflon-coated steel Wire Shelves included, Load per Shelf : 16 kg					
Ventilation		1ea of Ventilation hole with Stainless steel Cap, Hole Diameter 40mm					
Circulation		Gravity Convection Type					
Safety device		Over Temp. and Over Current Protector, Sensor Error Detector					
Others		UL/CUL Certified, CE Certified, GD-mark Storage Function (Temp. and Time) Alarm (Error Status and Timer-end)					
Net Weight (kg)		32	40	59	71		
Packing Size (w×d×h) (mm)		568×592×698	628×652×775	731×710×1,018	796×775×1,083		
Shipping Weight (kg)		39	53	67	78		
Power Consumption		159 W	169.9 W	292.9 W	420.5 W		
Energy Consum	ption, at 37°C	34 Wh	41 Wh	63 Wh	99 Wh		
	, at 50°C	81 Wh	103 Wh	152 Wh	212 Wh		
Power Supply		11	Phase 120V, 60H	z or 230V, 50/60	Hz		

* Other Specifications are available upon Customer's Request.

<Continued on next page>

Articles

< Continued from... DAIHAN ThermoStable™ SIG SMART Incubators, Gravity Convection-type>

Ordering Information

DH.SWIG03032 DH.SWIG03050 DH.SWIG03105 DH.SWIG03155	Incubator, Gravity, 230V, 32 Lit., "ThermoStable SIG-32" , 50 Lit., "ThermoStable SIG-50" , 105 Lit., "ThermoStable SIG-105" , 155 Lit., "ThermoStable SIG-155"		
DH.SWIG04032	Incubator, Gravity, 120V, 32 Lit., "ThermoStable SIG-32"		
DH.SWIG04050	, 50 Lit., "ThermoStable SIG-50"		
DH.SWIG04105	, 105 Lit., "ThermoStable SIG-105"		
DH.SWIG04155	, 155 Lit., "ThermoStable SIG-155"		
Snare Wire Shelves Tetlon Coated steel			

Spare Wire Shelves, Tetlon Coated steel

, DH.WIG11032	Wire Shelf, Teflon Coated steel, with 2 Brackets, for 32 Lit., "IGS032", w280 × d260mm
DH.WIG11050	Wire Shelf, Teflon Coated steel, with 2 Brackets, for 50 Lit., "IGS050", w340 × d310mm
DH.WIG11105	Wire Shelf, Teflon Coated steel, with 2 Brackets, for 105 Lit., "IGS105", w455×d375mm
DH.WIG11105	Wire Shelf, Teflon Coated steel, with 2 Brackets, for 155 Lit., "IGS155", w520 \times d440mm

Optional Wire Shelves, Stainless steel

DH.WIG12032	Wire Shelf, Stainless steel, with 2 Brackets, for 32 Lit., "IGSN032", w280 × d260mm
DH.WON11050	Wire Shelf, Stainless steel, with 2 Brackets, for 50 Lit., "ONS050", w340 × d310mm
DH.WON11105	Wire Shelf, Stainless steel, with 2 Brackets, for 105 Lit., "ONS105", w455 × d375mm
DH.WON11155	Wire Shelf, Stainless steel, with 2 Brackets, for 155 Lit/305Lit., "ONS155", w520 \times d440mm
	Validation (IQ, OQ) Service
DH.SWIG31032 DH.SWIG31050	Validation Service(IQ, OQ), "SIGV032", for "SIG-32" , "SIGV050", for "SIG-50"

"SIG\/050" for "SIG-50"

DH.3WIG31030	, 3137030,101 313-30
DH.SWIG31105	, "SIGV105", for "SIG-105"
DH.SWIG31155	, "SIGV155", for "SIG-155"

>>> DAIHAN WiRe[™] App & Web Service



WiRe[™] App & Web Service



SMART Incubator, Forced Convection-type "ThermoStable SIG-105"



Wire Shelves, Teflon Coated steel (Included)



Wire Shelves, Stainless steel (Optional)